

3000T

Log Max 3000T is a new generation thinning head best suited for long reach booms. This head features a new frame geometry, bringing forward the top part of the frame to prevent bark from clogging the measuring wheel.



3000T

STANDARD CONFIGURATION

METRIC

IMPERIAL

WEIGHTS & DIMS.	Weight (<i>Including Rotator Top & Link</i>)	623 kg	1,374 lbs
	Height (<i>Without Rotator & Link</i>)	132.5 cm	52.2"
	Maximum Width (<i>With Head Open</i>)	112.9 cm	44.5"
	Maximum Width (<i>With Head Closed</i>)	94.4 cm	37.2"

DRIVE SECTION	Number of Drive Rollers	2	
	Motor Size (<i>Drive Arm</i>)	398 cc 364 cc	24.3 in ³ 22.2 in ³
	Maximum Drive Roller Opening (<i>Diameter</i>)	394 mm	15.5"
	Maximum Drive Roller Closing (<i>Diameter</i>)	12 mm	0.5"
	Feed Speed	4.2 mps 4.6 mps	13.8 fps 15.1 fps

DELIMB SECTION	Maximum Delimb Opening	408 mm	16.1"
	Maximum Delimb Full Coverage	300 mm	11.8"
	Minimum Delimb Closing (<i>Diameter</i>)	12 mm	0.5"

BUTT SAW	Saw Type	218	
	Maximum Cut (<i>Diameter</i>)	51.6 cm	20.3"
	Bar Size	60 cm	23.6"
	Chain Pitch	0.404 mm	0.016"
	Motor Size	19 cc	1.16 in ³
	Chain Auto Tension	No	
	Oil Tank Capacity	4 L	1.1 gal

CARRIER REQS.	Maximum Pressure	250 bar	3,626 psi
---------------	------------------	---------	-----------

CONTROL SYSTEM	Model	Log Mate 510	
	Optional Additions	Yes	
	Full Optimization	Optional	
	Electronic Calipers (<i>For Electronic Calibrations</i>)	Optional	