M32 'PRELIMINARY'

Quadco's new 32-inch drum mulcher is the latest addition to a current lineup of tough, reliable and cost-efficient forestry mulching attachments. It is a versatile head, compact in dimensions but heavy duty, best suited to 8-15 ton excavators. To improve productivity and handling of ground material, a 100-degree lateral tilt is offered as standard equipment as well as a fixed heel equipped with replaceable bucket teeth. The drum is available with a variety of Quadco teeth, all-steel or carbide, to suit any application. The head will outproduce and outlive many other mass-produced brands, often built too light for professional contractors. Built-in universal boom adapter provides equipment dealers, particularly rental fleets, flexibility and quick turnarounds to meet the demands of their client's businesses - pins and sleeves only can be swapped when a change of carriers is required.





M32 'PRELIMINARY'

SPECIFICATIONS METRIC IMPERIAL

WEIGHT & DIMENSIONS

Weight (Incl lateral tilt, heel, typical bolt-on sleeves & pins)	770 kg	1,700 lbs
Overall Height	1,041 mm	41"
Width	610 mm	24.5"
Length	1,499 mm	59"
Lateral Tilt Angle	100° (+60°/-40°)	

Cutting Swath 813 mm 32"

Drum Diameter, Tip-to-Tip 457 mm 18"

Number of Teeth 18

Drum Speed 2,800 rpm

HYDRAULICS

Recommended Carrier Size	8 - 15 ton	
Variable Displacement Motor	60 or 85 cc	
Minimum Flow @ Pressure	65 l/min @ 240 bar	17 gpm @ 3,500 psi
Optimum Flow @ Pressure	140 l/min @ 240 bar	37 gpm @ 3,500 psi
Maximum Pressure	340 bar	5,000 psi







